

Tahoe Direct-Vent Fireplaces Premium Clean-Face Multisided Series Peninsula and See-Through

Premium Clean-Face Direct-Vent See-Through Fireplace (DVCP36SP) with Rustic Brick with Soldier Course Liner and Campfire Logs, installed in Custom Stone Surround



Premium Clean-Face Multisided Series

A Great View from Any Angle

Both Peninsula and See-through models feature an attractive clean-face design that integrates the barrier screens into the fireplace – flush with the fireplace face – allowing you to install tile, brick, or other non-combustible materials right up to the fireplace opening.

Choose between the hand-painted Campfire Logs or Mixed Logs and Stones to customize your fireplace. Both multi-sided fireplaces are rated at 34,000 Btu (Nat) / 34,000 Btu (LP), and include non-combustible board for installation above the fireplace. Additional non-combustible materials may be required. See installation manual.



Premium Clean-Face Direct-Vent See-Through Fireplace (DVCP36SP) with Rustic Brick with Soldier Course Liner, and Campfire Logs, Installed in Custom Stone Surround

Premium Clean-Face Direct-Vent Peninsula Fireplace (DVCP36PP) with Black Fluted Liner and Mixed Stones and Logs, Installed in Custom Surround



Options & Accessories

Liners

For Premium Clean-Face Tahoe multi-sided fireplace models, choose a hand-painted ceramic fiber liner in Rustic Brick with Soldier Course, or Fluted Black. Or select a Black Porcelain liner to enhance the illusion of flame and depth.







Black Fluted



Black Porcelain

Lighting Kit & Blower

The available lighting kit draws attention to the intricate details in the log set and liner – even when no fire is burning. Enhance heat distribution with the optional variable-speed blower. Both the light and blower include a rheostat control.



Optional Lighting Kit



Optional Variable-Speed Blower

Control Options

Your Peninsula or See-Through Tahoe Clean-Face Fireplace is available in Millivolt – with a standing pilot for simple, reliable operation all winter long. Or choose our energy-saving Intermittent Pilot ignition. The IP system includes battery backup to operate in a power outage and can switch to a standing pilot to warm your home during an extended power failure. Both the Millivolt and IP systems work with our control accessories – from a simple on/off remote to a thermostat to a programmable thermostat remote.



FRBTPS Thermostat Remote Control Millivolt or IP



FRBC Remote Control Millivolt Only



FRBTC2 Thermostat Remote Control Millivolt or IP



RVKP or RVKN Remote Control IP Only



TRW Wall Thermostat



TMV Wall Thermostat





FWS Wall Switch

Direct-Vent Premium Peninsula Fireplace Dimensions

| Model | A Max Height | B Max. Width | C Max. Depth | D Height | E Width | F Interior Depth | H Height to Standoffs | U Viewing Area Width | V Viewing Area Height | X Viewing Area Width - Sm |
|------------|-----------------|-----------------|-----------------|-------------|------------|---------------------|-----------------------------|----------------------------|------------------------------------|---------------------------------|
| DVCP36PP30 | 39 1/4 | 42 | 24 | 31 1/2 | 37 1/4 | 20 1/4 | 42 3/8 | 33 5/8 | 25 | 18 5/8 |
| DVCP36PP70 | 39 1/4 | 42 | 24 | 31 1/2 | 37 1/4 | 20 1/4 | 42 3/8 | 33 5/8 | 25 | 18 5/8 |










Direct-Vent Premium See-Through Fireplace Dimensions

| Model | A Max Height | B Max. Width | C Max. Depth | D Height | E Width | F Interior Depth | H Height to Standoffs | U Viewing Area Width | V Viewing Area Height |
|------------|------------------------|-----------------|-----------------|-------------|------------|---------------------|-----------------------------|----------------------------|------------------------------------|
| DVCP36SP30 | 39 1/4 | 45 | 24 | 31 1/2 | 37 1/4 | 20 1/4 | 42 3/8 | 33 5/8 | 25 |
| DVCP36SP70 | 39 1/4 | 45 | 24 | 31 1/2 | 37 1/4 | 20 1/4 | 42 3/8 | 33 5/8 | 25 |







Minimum Fireplace Opening Dimensions

| Model | Α | В | С |
|----------|--------|--------|----|
| DVCP36PP | 42 1/2 | 41 3/4 | 23 |
| DVCP36SP | 42 1/2 | 45 1/2 | 23 |





| Gas Inlet | | | | | |
|-------------------------|----------------------------|--|--|--|--|
| Type of Gas | Natural or LP | | | | |
| Iron Pipe Size (N.P.T.) | 1/2 inch | | | | |
| Gas Inlet | Standing Pilot/Piezo or IP | | | | |
| | | | | | |

Warranty for All Models

10-year limited warranty on combustion chamber, limited lifetime on glass. All other parts carry a three-year limited warrany.

All remote controls carry a one-year limited warranty.

All direct-vent fireplaces manufactured after January 1, 2015, must be installed with a barrier screen to prevent accidental contact with hot glass. Depending on the fireplace model, the barrier screens are available separately or incorporated into decorative fronts. See Owner's Manual for details.

Refer to your Owner's Manual for complete installation and safety information

Empire is committed to continuous product improvement; specifications are subject to change without notice. Dimensions in this brochure are approximate; read and follow the framing dimensions in the owners manual supplied with your Empire product.

ber of the following industry association













This appliance is design-certified to the ANSI standard by:





SINCE 1932
Empire Comfort Systems Inc.
918 Freeburg Ave.
Belleville, IL 62220-2623
info@empirecomfort.com
WMH-00981 3/15/19

The Empire Comfort Systems and White Mountain Hearth names and logos are registered U.S. trademarks